

Crucible Lifter “Nolti-Lift 900”

Safe lifting and easy installation of new crucibles

Introduction

The “Nolti-Lift 900” fits perfectly to all crucibles up to a wall-thickness of 65mm (2,53”).

The space-saving design works with just 45mm clearance between the outer crucible wall and the furnace lining.

Due to its new design and unique slip resistant surface coating, which is permanently affixed with the lifter arms, highest level of safety and best practice in daily use is guaranteed.

The “Nolti-Lift 900”, with three brackets, can lift crucibles up to 900kg (1984lb) with an outer diameter from 515mm (20,28”) up to a maximum of 1780mm (70,07”).

Attention: Standing under suspended load is forbidden!
Not suitable for lifting warm or used crucibles!



Advantages

- Easy to use due to self-tensioning
- Safe grip due to slip resistant, coated brackets
- Tested and approved by our customers
- Usable even in constricted conditions
- CE-Certification

Sizes

The „Nolti-Lift 900“ is available in one size

Item-number	Outer diameter in mm from	Outer diameter in mm to	Max. lifting capacity in kg
1800000184	ø 515 (20,28”)	ø 1780 (70,07”)	900 (1984lb)

Quality

Our crucible lifters are CE certified and made from premium grade raw materials under an ISO 9001:2015 quality management system.

For more information, contact us today.